



TH-160	
Rated voltage:	220V/ 50/60Hz
Rated power:	2100W
Heater power:	1200W
Facer power:	900W
Max. temp.:	270°C
Temp.Tolerance:	≤5°C
Welding size:	63-160mm
Suit material:	PP-R/PE/PB
Weight:	52.2 kgs
Packing:	Wooden case
Volume:	0.2 CBM



TH-200	
Rated voltage:	220V/ 50/60Hz
Rated power:	2100W
Heater power:	1200W
Facer power:	900W
Max. temp.:	270°C
Temp.Tolerance:	≤5°C
Welding size:	90-200mm
Suit material:	PP-R/PE/PB
Weight:	66.2 kgs
Packing:	Wooden case
Volume:	0.28 CBM



TH-250	
Rated voltage:	220V/ 50/60Hz
Rated power:	2410W
Heater power:	1210W
Facer power:	1200W
Max. temp.:	270°C
Temp.Tolerance:	≤5°C
Welding size:	90-250mm
Suit material:	PP-R/PE/PB
Weight:	130.6 kgs
Packing:	Wooden case
Volume:	0.55 CBM



THD-160	
Rated voltage:	220V/ 50/60Hz
Pressure range:	0-6.3Mpa
Rated power:	2750W
Heater power:	1200W
Facer power:	900W
Hydraulic power:	650W
Max. temp.:	270°C
Temp.Tolerance:	≤5°C
Welding size:	63-160mm



Suit material:	PP-R/PE/PB
Weight:	110kgs
Packing:	Wooden case
Volume:	0.43 CBM

**THD-250**

Rated voltage:	220V/ 50/60Hz
Pressure range:	0-6.3Mpa
Rated power:	3950W
Heater power:	2000W
Facer power:	1200W
Hydraulic power:	750W
Max. temp.:	270°C
Temp.Tolerance:	≤5°C
Welding size:	90-250mm
Suit material:	PP-R/PE/PB
Weight:	147.6kgs
Packing:	Wooden case
Volume:	0.63 CBM

**THD-315**

Rated voltage:	220V/ 50/60Hz
Pressure Range:	0-6.3Mpa
Rated power:	4950W
Heater power:	3000W
Facer power:	1200W
Hydraulic power:	750W
Max. temp.:	270°C
Temp.Tolerance :	≤5°C
Welding size:	90-315mm
Suit material:	PP-R/PE/PB
Weight:	187.3 kgs
Packing:	Wooden case
Volume:	0.74 CBM

**THD-450**

Rated voltage:	380V/ 50/60Hz
Pressure Range:	0-6.3Mpa
Rated power:	9500W
Max. temp.:	270°C
Temp.Tolerance :	≤5°C
Welding size:	250-500mm
Suit material:	PP-R/PE/PB
Weight:	460 kgs
Packing:	Wooden case
Volume:	2.33 CBM

**THD-630**

Rated voltage:	380V/ 50/60Hz
----------------	---------------



Pressure Range:	0-6.3Mpa
Rated power:	12.2KW
Heater power:	9200W
Facer power:	1500W
Hydraulic power:	1500W
Max. temp.:	270°C
Welding size:	315-630mm
Suit material:	PP-R/PE/PB
Weight:	610 kgs
Packing:	Wooden case
Volume:	2.66 CBM



THDRHJ-3500	
Input voltage:	175-250V/ 50/60Hz
Output voltage:	39.5V Ac
Output power:	3.5KW
Working temp.:	- 15-50°C
Hydraulic power:	1.5KW
Max. temp.:	270°C
Relative Humidity:	≤80%
Time adjust range:	1-9999s
Data storage:	100 times
Packing:	400×290×350(mm)
Weight:	27kgs



Including:
1 machine
1 facer
1 heater plate
1 holder
1 set clamps:
63.75.90.110.125.140.160 mm

=

Including:
1 machine
1 facer
1 heater plate
1 holder
1 set clamps:
90.110.125.140.160.180.200 mm

Including:
1 machine
1 facer
1 heater plate
1 holder
1 set clamps:
90.110.125.140.160.180.200.225.250 mm

Including:
1 machine
1 facer
1 heater plate
1 holder
1 hydraulic pump
1 set clamps:
63.75.90.110.125.140.160mm

Including:
1 machine
1 facer
1 heater plate
1 holder
1 hydraulic pump
1 set clamps:
90.110.125.140.
160.180.200.225.250mm

Including:
1 machine
1 facer
1 heater plate
1 holder
1 hydraulic pump
1 set clamps:
90.110.125.140.
160.180.200.225
250. 280.315

Including:
1 machine
1 facer
1 heater plate
1 holder
1 hydraulic pump
1 set clamps:
250. 280.315.355.400.450

Including:

1 machine
1 facer
1 heater plate
1 holder
1 hydraulic pump
1 set clamps: 315.355.400.450.500.560.630 mmm

Including:
1 machine only
1 Scanner

